



Characteristic Curves

TEN 40-1210


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-1210


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-1211


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-1211


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-1212


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-1212


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-1220


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-1220


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-1222


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-1222


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-1223


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-1223


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-1233


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-1233


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-1234


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-1234


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-1231


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-1231


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-1232


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-1232


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2410


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-2410


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2411


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-2411


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2412


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-2412


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2420


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-2420


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2422


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-2422


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2423


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-2423


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2433


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-2433


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2434


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-2434


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2431


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-2431


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-2432


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-2432


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4810


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-4810


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4811


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-4811


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4812


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-4812


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4820


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-4820


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4822


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-4822


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4823


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-4823


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4833


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-4833


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4834


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-4834


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4831


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature (with Heatsink TEN-HS3)




TEN 40-4831


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 40-4832


Efficiency versus Output Load




Power Dissipation versus Output Load




Efficiency versus Input Voltage



Derating Output Load versus Ambient Temperature




Derating Output Load versus Ambient Temperature
(with Heatsink TEN-HS3)




TEN 40-4832


Typical Output Ripple and Noise
(with external capacitor; see datasheet)



Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic



Remote on/off Voltage Start-Up Characteristic

