

Product Change Note


Date January 19, 2023
No. 039-22

TRACO POWER TPP 15-D, TPP 15-J, TPP 15A-D, TPP 15A-J

To whom it may concern

Specifications change due to new component

Due to a component discontinuation, TPP 15 series will be equipped with a new PWM controller. For doing so, PCB layouts have undergone necessary changes. The new PWM controller and the layout adjustments lead to some specification changes:

	Current version	New version
Product picture <i>Through hole device</i> TPP 15-D TPP 15A-D		
Product picture <i>with JST connectors</i> TPP 15-J TPP 15A-J		
Leakage current (at 264Vac)	70µA typ. (75µA max.)	70µA typ. (100µA max.)
Switching frequency	75-95kHz (85kHz typ.)	90-110kHz (100kHz typ.)
Start-up time	at 230Vac 500ms max. (250ms typ.)	850ms max. (650ms typ.)
Over voltage protection	130% typ. (125-140% of Vout)	130% typ. (115-140% of Vout)
No load consumption	at 230Vac 75mW max.	100mW max.

Timeline:

The product change is proposed to be implemented till production date: during Q2/2024.
 Prototype availability: May 2023

Datasheets and application notes are available on the respective product pages for [TPP 15-D series](#), [TPP 15-J series](#), [TPP 15A-D series](#) and [TPP 15A-J series](#).

For more information contact your local TRACO POWER sales representative or Distributor.
We apologize for any resulting inconvenience and thank you for your understanding.

Simeon Tresp
Product Manager