

INSTALLATION INSTRUCTIONS

TMLM 10xxx & TMLM 20xxx Series

Order Code	Output Power max.	Output
TMLM 10103	8.25 Watt	+3.3Vdc / 2.500A
TMLM 10105	10.00 Watt	+5.0Vdc / 2.000A
TMLM 10112	10.00 Watt	+12.0Vdc / 0.830A
TMLM 10115	10.00 Watt	+15.0Vdc / 0.666A
TMLM 10124	10.00 Watt	+24.0Vdc / 0.420A

Switching Power Supply

Order Code	Output Power max.	Output
TMLM 20103	12.0 Watt	+3.3Vdc / 3.600A
TMLM 20105	18.0 Watt	+5.0Vdc / 3.600A
TMLM 20112	20.0 Watt	+12.0Vdc / 1.660A
TMLM 20115	20.0 Watt	+15.0Vdc / 1.330A
TMLM 20124	20.0 Watt	+24.0Vdc / 0.833A

Input Voltage Range:	90 – 264Vac / 47 – 440Hz	Terminal for wiring:	PCB mounting with solder pin's
	120 – 370Vdc	Safety according IEC/EN 60536:	Safety Class II prepared
Input current at Vin = 115Vac	TMLM 10xxx = 0.220A typ		TMLM 20xxx = 0.385A typ
Input current at Vin = 230Vac	TMLM 10xxx = 0.150A typ		TMLM 20xxx = 0.280A typ
Output voltage accuracy	±2.0%	Case material:	Plastic Resin + Fiberglas UL 94V-0 flammability rating
Operating temperature range:	-25°C – +60°C max.		
Output Power Derating:	TMLM 10xxx above +50°C → 3.75%/°C	External fuse:	1.5A slow blow type
	TMLM 20xxx above +40°C → 2.50%/°C		

Safety Instructions:

- Before installation read these instructions carefully and completely. This installation instruction cannot claim for every possible example of installation, operation or maintenance. Further information's are obtainable from your local distributor office or from the product data sheet which can be downloaded from the Internet at <http://tracopower.com>.
- The power supplies are constructed in accordance with the safety requirements of IEC/EN/UL60950-1. They fulfil the requirements of the Low Voltage Directive (LVD) and carries the CE-mark. They are UL and cUL approved in accordance to UL60950-1 (recognised).
- Before any installation, maintenance or modification work ensure that the main switch is switched off and prevented from being switched on again. In case of non-observance touching at any alive components or improper dealing with this power supply can result in death, severe personal injury or substantial property damage. The successful and safe operation is dependent on proper storage, handling, installation and operation.
- Compliance with the relevant national regulations (in the USA, Europe and the other countries) must be ensured. Before operation is started the following conditions must be ensured:
 - ❖ Connection to mains supply in compliance with national regulations (VDE0100 and EN50178).
 - ❖ Power supply must be sufficiently fused.

- ❖ All output tracks must be rated for the power supply output current and must be connected with the correct polarity.
- ❖ Sufficient cooling must be ensured.
- ❖ Keep away from fire and water

- **Never work on the power supply if power is supplied!** Risk of electric arcs and electrical shock which can cause death, severe personal injury or substantial property damage.
- **Warning:** Hazardous voltages and components storing a very substantial amount of energy are present in this power supply during normal operating conditions. However, these are inaccessible. Improper handling may result in an electric shock or serious burns!

Do not work on or around the power supply until at least 5 minutes after it has been disconnected from the mains on all poles.

Installation Instructions:

- This power supply is designed for professional indoor systems. In operation the power supply must not be accessible. It may be installed and put into service by qualified personnel only.
- The correct mounting position for optimal cooling performance must be observed. Observe power derating. (see data sheet)
- **Recycling:** The unit contains elements which are suitable for recycling, and components which need special disposal. You are therefore requested to ensure that the power supply will be recycled by the end of its service life.