



Characteristic Curves

TPP 30-103A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response to Dynamic Load Change (25%) at 115 Vin




Transiente Response to Dynamic Load Change (25%) at 230 Vin




TPP 30-103A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-105A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output Load versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response to Dynamic Load Change (25%) at 115 Vin




Transiente Response to Dynamic Load Change (25%) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-105A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-109A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin




Transiente Response (25% load step) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-109A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-112A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin




Transiente Response (25% load step) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-112A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-115A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-124A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin




Transiente Response (25% load step) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-124A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-136A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin




Transiente Response (25% load step) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-136A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-148A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin




Transiente Response (25% load step) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TPP 30-148A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin



Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin



Typical Hold-Up Characteristic at 230 Vin

