



Characteristic Curves

TIM 3.5-0911(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TIM 3.5-0919(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25 $^{\circ}C$ after warm-up time unless otherwise stated.

TIM 3.5-0912(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-0913(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-0915(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-0922(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-0923(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-1211(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-1219(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-1212(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-1213(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-1215(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-1222(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-1223(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-2411(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-2419(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-2412(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-2413(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-2415(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-2422(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-2423(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-4811(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-4819(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-4812(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-4813(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-4815(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-4822(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TIM 3.5-4823(SM)


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic



Remote on/off Voltage Start-Up Characteristic

